



Eur päisches Pat ntamt
European Patent Offic
Office eur péen d s brev ts



(11) Publication number:

0 565 049 A1

EUROPEAN PATENT APPLICATION

(21) Application number: 93105678.2

(51) Int. Cl.⁵: **A61B 17/28**

(22) Date of filing: 06.04.93

(30) Priority: 06.04.92 US 863951

(43) Date of publication of application:
13.10.93 Bulletin 93/41

(84) Designated Contracting States:
DE FR GB IT

(71) Applicant: United States Surgical Corporation
150 Glover Avenue
Norwalk, Connecticut 06856(US)

(72) Inventor: Nicholas, David A.
148 Cottage Street
Trumbull, CT 06611(US)

(74) Representative: Marsh, Roy David et al
Hoffmann Eitle & Partner,
Patent- und Rechtsanwälte,
Postfach 81 04 20
D-81904 München (DE)

(54) Surgical instrument locking mechanism.

(57) An endoscopic or laparoscopic surgical instrument (1) having an internally disposed locking mechanism located within a barrel portion (8) of a handle assembly (2). The instrument includes a handle assembly (2) having a pivoting handle (6) and a stationary handle (7), a barrel portion (8) to which an elongated body assembly (3) is secured, and a locking mechanism for releasably positioning a tool mechanism (30) located at the distal end of the body

assembly. In one embodiment the locking mechanism comprises a trigger (12), a brake (14) and a latch spring (15). In another embodiment the locking mechanism comprises a latch spring (15) and a locking block. A rotational knob (18) and locking member may also be provided to position the body assembly at various orientations to the longitudinal axis.




FIG. 3

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to surgical instruments, and more particularly relates to a handle for an endoscopic or laparoscopic surgical instrument having a novel locking mechanism which is internally disposed within the handle to provide for incremental positioning of the jaw members of a surgical instrument in relation to each other. The positioning and subsequent release of the jaw members is accomplished through the provision of a trigger mechanism disposed within the handle.

2. Discussion of the Prior Art

In the prior art, various endoscopic surgical instruments are disclosed which utilize generally complex mechanisms for opening and closing handle members which actuate jaw members to facilitate use of the device at a surgical site. Many devices provide an intricate construction in which a linkage mechanism for opening and closing the jaws requires numerous moving parts, while a sliding arrangement is provided between two extended rod members to activate the linkage mechanism in response to movement of the handle members. In addition, pivoting of the handle members in many cases causes an unwanted radial torquing force on the rod which requires additional space to be provided in the handle members to accommodate the deflected radial movement of the rod.

Furthermore, it is often necessary for the surgeon, or an assistant, to maintain a constant force on the handles to keep the jaw mechanism closed in the event that the instrument is a grasping or gripping device such as forceps, needle holders, or retractors. This limits the surgeon's range, and in the case of an assistant, often requires additional personnel to be present in the operating room, thus restricting movement in an already confining location. To alleviate this problem, it has been known to provide locking mechanisms on the handles of the surgical instruments which allow the surgeon to lock or clamp the jaw members in place to free his hands to operate additional instruments during the course of the operation. Furthermore, this frees the surgical assistant to support the surgeon and eliminates the need for additional assistants. Typical locking devices include arm members which extend between the handles so that a series of ridges or ribs on each arm member engage corresponding ridges on the opposite arm to lock the handles in position. Bending one arm in relation to the other releases the locking mechanism.

A disadvantage associated with these devices concerns the release of the locking mechanism for

subsequent movement of the jaw members to remove or reposition the instrument. Generally, the arm members of locking mechanisms are constructed of a resilient material, such as stainless steel or rigid plastic, and the locking forces which hold the arm members in engagement are generated by the natural flexing and biasing of the material of which the arm members are constructed. To release the locking mechanism, the arms must be disengaged by overcoming the locking forces of the arms. Typically, this is accomplished by manually flexing the arms away from each other, necessitating the use of two hands, one to grasp the instrument, and the other to forcibly move the arm members. This, of course, requires the surgeon (or assistant) to cease what he is doing and release the mechanism, thus reducing the effectiveness of the surgeon during the operation, particularly in an emergency situation.

Finally, locking mechanisms located on the handles require special care in sterilization, packaging and storage, as well as in normal handling in the operation room. Dirt and debris may clog the ribs of the locking mechanism thus reducing its effectiveness, and damage to the ribs during storage or packaging may destroy the ribs, rendering the locking mechanism useless.

U.S. Patent No. 1,452,373, to Gomez discloses a typical locking mechanism for a surgical instrument, in which a plurality of ribs are provided on an extension of the handle member which engage a similar rib member on the opposite handle. Once engaged, the handles must be moved away from each other perpendicular to their longitudinal axis to disengage the locking mechanism to release the jaw mechanism.

U.S. Patent No. 4,896,661, to Bogert et al. discloses a surgical instrument having a ratchet mechanism positioned on the handle members which includes a curved rack member attached to one handle member which passes through a slot in the other handle member. A releasable pawl member is provided on the second handle to engage the rack member and provide a means for releasing the ratchet.

U.S. Patent No. 4,935,027, to Yoon discloses a surgical instrument having a ratchet mechanism positioned between the handle members. A rack member is provided which extends from one handle and passes through a slot in the second handle to lock the handles in place. Pivoting the rack member away from corresponding grooves in the slot will release the ratchet mechanism.

U.S. Patent No. 4,428,374, to Auburn discloses a surgical instrument having means for positioning and holding the handle members in relation to each other. A rack member is provided on one handle member which extends through a slot in the sec-

ond handle member in which a releasable pawl mechanism is provided to engage and disengage the rack member.

The novel surgical instrument pursuant to the present invention obviates the disadvantages encountered in the prior art and provides a precise instrument which is easy to manufacture and efficient to use, which eliminates the need for an external locking device and provides for one hand operation of the surgical instrument through manipulation of the opposing handles and a trigger mechanism. The instrument of the present invention incorporates many features which are of use to the surgeon during an operation, including a means for rotating the jaws in relation to the handle if desired, while maintaining a lightweight construction in an easy to handle device in which all of the features may be operated with one hand. Furthermore, the features are positioned so as to provide a maximum line of sight for the surgeon without obstructing the view to the surgical site.

SUMMARY OF THE INVENTION

The present invention provides a novel endoscopic or laparoscopic surgical device which incorporates many features necessary for endoscopic or laparoscopic surgical procedures, and provides a lightweight and easy to use device which may be operated with one hand. The device includes an internal locking mechanism located preferably within the handle mechanism which provides for the locking of the jaws of the instrument in any position necessary for performing the surgical procedure. The locking mechanism is activated by and deactivated by a trigger member situated on the handle assembly by pulling on the trigger member. The device is simple to manufacture, and may incorporate any one of a series of jaw mechanisms for various surgical procedures. The device is a high precision instrument in which many moving parts normally associated with such a device are eliminated, thus reducing instances of mechanical failure requiring expensive repair or ultimate destruction of the instrument.

The endoscopic or laparoscopic surgical instrument employing the locking mechanism of the present invention essentially comprises of a handle assembly, and elongated body assembly, a tool mechanism at an end of the body assembly remote from the handle assembly, and the locking mechanism and associated trigger member within the barrel portion of the handle assembly. The trigger extends out of the barrel portion of the handle assembly adjacent the pivoting and the stationary handle portions of the handle assembly. The body assembly consists of an outer tubular member and an inner rod member which coaxially

passes within the outer tubular member. The rod member is attached to the pivoting handle, through the provision of a rotatable connecting means on the pivoting handle. As the handle moves, the connecting means rotates to allow the inner rod to move longitudinally in the outer tube with minimal radial deflection, thereby allowing for the reduction of the required internal spacing between the outer tube and inner rod to result in a more compact and streamlined instrument. Furthermore, unwanted torquing forces are eliminated at the connecting means thus minimizing the possibility of mechanical breakdown of the instrument at the connection between the pivoting handle and the movable inner rod. The tubular member is secured in a conventional manner to the barrel portion which extends into the stationary handle. As the pivoting handle moves, the rod member slidably reciprocates within the outer tube member.

Attached to a distal end of the body assembly is the tool mechanism which opens and closes in response to movement of the pivoting handle in relation to the stationary handle. The tool mechanism may comprise a pair of jaw members wherein one or both jaw members open and close to perform various endoscopic or laparoscopic surgical procedures. The jaw mechanism includes, but is not limited to, a scissors device, a dissecting device, a grasping device, a retractor device, and like mechanisms.

The present invention provides a locking mechanism in the form of a trigger to arrest movement of the inner rod to incrementally position the jaws in relation to each other. The locking mechanism is provided on the barrel portion of the handle assembly and is positioned so that the surgeon may activate the lock mechanism with a single hand. Preferably, the trigger moves linearly to minimize the required spacing within the handle.

Alternately, the locking mechanism of the present invention provides a trigger mechanism which may be operable by a pivoting motion of the trigger as opposed to a linear motion of the trigger. In a further embodiment, the locking mechanism is entirely internal, such that the trigger itself is eliminated.

The present invention also includes the provision of a rotatable knob on the outer tubular member to allow the body assembly and jaw mechanism to rotate to position the jaws at desired angles to the longitudinal axis during the surgical procedure. Preferably, the rotatable knob is secured to the outer tube and positioned in a slot which passes through the barrel portion of the stationary handle, so that a surgeon may rotate the knob, and consequently the body assembly and jaw mechanism, through the use of his thumb while he is holding the stationary handle with his fingers. This

frees the surgeon's other hand to simultaneously operate another instrument during surgery.

The present invention may also feature a connection port to provide the device with electrocautery capabilities. A connection port allows for the connection of a suitable jack member to be inserted into the device. The outer tube of the body assembly is provided with electrical insulation, such as heat shrink tubing, which extends a substantial portion of the length of the outer tube. In this embodiment, the handle is molded of plastic material to provide electrical insulation for the user.

In the preferred embodiment, all the above features are incorporated into a single endoscopic and laparoscopic surgical instrument, so that the instrument has electrocautery, rotational, and locking capabilities. However, the instrument of the present invention is constructed with at least the locking capabilities to provide for the locking and unlocking of the surgical instrument during a surgical procedure.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing objects and other features of the invention will become more readily apparent and may be understood by referring to the following detailed description of illustrative embodiments of the endoscopic or laparoscopic surgical instruments having an internal locking mechanism, taken in conjunction with the accompanying drawings, in which:

Figure 1 illustrates a perspective view of a first embodiment of an endoscopic or laparoscopic surgical instrument incorporating a locking mechanism of the present invention;

Figure 2 illustrates an exploded perspective view of the instrument of Figure 1 showing in detail the locking mechanism according to the present invention;

Figure 3 illustrates a side plan cut-away view of the handle assembly containing the locking mechanism of the embodiment of Figure 1;

Figures 4a-4e illustrate a top plan view of the trigger and latch release spring of the embodiment of Figure 1 in operation from activation through release of the locking mechanism;

Figure 5 illustrates a side plan view and partial cut-away view of the trigger of the embodiment of Figure 1;

Figure 6 illustrates a side plan view of the latch release spring of the present invention;

Figure 7 illustrates a perspective view of an endoscopic or laparoscopic surgical instrument possessing the locking mechanism according to a second embodiment of the present invention;

Figure 8 illustrates an exploded perspective view of the instrument of Figure 7 showing in

detail a second embodiment of the locking mechanism according to the present invention; Figures 9a-9e illustrate a bottom plan view of the locking mechanism and release spring of the embodiment shown in Figure 8 in operation from activation through release of the locking mechanism;

Figure 10 illustrates a perspective view of the locking mechanism and release spring of the embodiment shown in Figure 8; and

Figure 11 illustrates a plan view of the brake member of the locking mechanism of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now in specific detail to the drawings, in which like reference numerals identify similar or identical elements, Figure 1 illustrates a first embodiment of the endoscopic or laparoscopic surgical instrument 1. In its simplest form, device 1 comprises a handle assembly 2, a body assembly 3, a trigger 12, and an internal locking mechanism assembly (not shown) associated with trigger 12. Handle assembly 2 comprises a pivoting handle 6 and a stationary handle 7 having a barrel portion 8. Body assembly 3 essentially comprises an outer tubular member 22 through which an inner rod member 21 coaxially passes in a slidable arrangement. Outer tube member 22 is secured to barrel portion 8 and remains stationary during operation of the device, so that upon movement of pivoting handle 6, the inner rod 21 reciprocates within tube member 22 to operate a tool mechanism 30 provided at the distal end of the instrument 1. Tool mechanism 30 may comprise any surgical implement, such as scissors device, a grasping device, a forceps device, a retractor device and like mechanisms. Connecting means 9 connects the inner tube member 22 with the pivoting handle 6. Connecting means 9 also provides a rotatable connection means for inner rod 21 during its reciprocating movement within outer tubular member 22, to limit or minimize radial deflection of rod 21 during movement. A rotation knob 18 may be provided which rotates body assembly 3 to orient tool mechanism 30 at various angles to the longitudinal axis.

As best seen in Figures 2 and 3, the locking mechanism assembly provides for retaining the jaw mechanism 30 of the surgical instrument in various positions by pulling on trigger 12 in a direction toward the handle, or proximal, end of the instrument. Trigger 12 provides a simple and effective means of locking and unlocking the jaw mechanism 30 of the surgical instrument during a surgical procedure using only one hand. The locking

mechanism assembly, except for the lower portion of trigger 12, is positioned internally within barrel portion 8 and stationary handle 7 so that none of the mechanism is exposed to environmental conditions.

The locking mechanism assembly includes a trigger 12, a brake 14 which is adapted to pivot with respect to pin 13, and biasing spring 10 which is adapted to bias brake 14 towards the tool mechanism, or distal end, of the instrument 1. Trigger 12 and biasing spring 17 bias the locking mechanism to the unlatched position, and operate in association with latch release spring 15, whose function will be described below.

In use, the surgeon will decide whether or not the distal jaws should lock in a closed configuration upon tissue. If not, trigger 12 remains in its distal, rest position and the jaws freely open and close upon manual operation of pivotal handle 6. Conversely, if the surgeon desires that the jaws should lock, the surgeon draws trigger 12 proximally with his finger. In the embodiment shown in Figs. 1-3, trigger 12 is moved linearly in a plane parallel to the inner rod 21 and the longitudinal axis of the instrument 1. This proximal movement of trigger 12 allows brake 14 to pivot in a distal direction under the influence of spring 10 such that the aperture 24 (See Fig. 12) in the upwardly extending portion of brake 14 becomes eccentric with respect to center rod 21 which passes therethrough. This eccentricity causes rod 21 to be frictionally retained with respect to distal motion of rod 21. However, rotation of pivotal handle 6 towards stationary handle 7, which translates to proximal motion of center rod 21, is unencumbered since the brake 14 has freedom of motion in the proximal direction, as against compression spring 10. In this manner, the position of the jaws may be adjusted incrementally. Since the spring force of spring 17 is greater than the spring force of spring 10, retention of rod 21 results in locking of the jaws 30 only when latch spring 15 engages recess 42 of cam member 40 which is integral to trigger 12. (See Figure 4).

Turning to Figs. 4a-4e, the operation of latch release spring 15 is illustrated wherein latch spring 15 is adapted to ride against the upwardly projecting diagonal cam member 40 on trigger 12. As seen in Figs. 4a-4c, trigger 12 moves proximally so that latch release spring 15 rides along cam surface 41 until the distal end of the cam surface is reached, at which point the spring bias of the latch release spring 15 brings latch released spring 15 into a locking engagement within triangular recess 42 cut into the cam member 40 on trigger 12. It is this engagement of latch release spring 15 with the triangular recess 42 on trigger 12 that maintains the trigger in its proximal position and allows the jaws to lock because, as noted above, this proximal

movement of trigger 12 allows brake 14 to pivot distally to engage aperture 24 with rod 21 under the bias of compression spring 10.

When the surgeon wishes to unlock the gripping jaws, he pulls trigger 12 further in the proximal direction. This proximal movement causes latch release spring 15 to contact triangular release 43 cam at the front edge of trigger 12, as seen in Fig. 4d. This moves the latch release spring 15 over cam member 40, and allows it to then ride on cam surface 44 on the opposite side of the cam member 40 (see Fig. 4e) when the surgeon releases his finger from trigger 12. Thus, trigger 12 is allowed to move distally under the bias of compression spring 17, thereby moving brake 14 in a proximal direction such that the aperture 24 becomes concentrically aligned with center rod 21.

Figure 5 illustrates the trigger 12 of one embodiment of the invention showing the location of diagonal cam member 40 and triangular release cam 43. Also shown is the cavity 46 for compression spring 17 (not shown).

Figure 6 illustrates a side view of one embodiment of the latch release spring 15. Figure 6 further illustrates mounting plate 81 and latch release spring finger 82.

Figure 7 illustrates another embodiment of the endoscopic or laparoscopic surgical instrument 100, which is identical to the embodiment of Figure 1 except that trigger 12 is eliminated and a different tool mechanism is illustrated. In this embodiment, the locking mechanism is incorporated internally within the handle assembly and the body assembly, and not as an independent mechanism as in the embodiment of Figure 1, to allow for the locking mechanism to lock the surgical instrument only in a fully closed position. Upon movement of pivoting handle 116, the inner rod assembly 121 reciprocates within outer tube assembly 119 to operate a tool mechanism 130 provided at the distal end of the instrument 100. This tool mechanism 130 may comprise any surgical implement, such as a scissors device, a grasper device, a forceps device, a retractor device and like device mechanisms. A rotation knob 126 may be provided which rotates body assembly 113 to orient the tool mechanism at various angles to the longitudinal axis.

In use, when the surgeon desires that the jaws should lock, the surgeon draws pivoting handle 116 toward stationary handle 117 with his thumb. This movement of pivoting handle 116 allows latch release spring 140 to lock in triangular recess 152 of cam member 150 on locking block 141.

Turning to the operation of latch release spring 140, as best seen in Figs. 9a-9e, this spring is adapted to ride against diagonal cam surface 151 on locking block 141. As locking block 141 moves

proximally, latch release spring 140 pivots into locking engagement within a triangular recess 152 of member 150 on locking block 141. It is this engagement of latch release spring 140 with the triangular recess 152 on locking block 141 that maintains the pivoting handle and the jaw mechanism in the locked position.

When the surgeon wishes to unlock the gripping jaws, he squeezes pivoting handle 116 further which causes latch release spring 140 to contact a triangular release cam 153 at the front edge of locking block 141. Inner rod 121 is preferably constructed as a two-piece member as shown. Rod 121a is secured to rod 121b by pin 160 which rides in slot 162, which allows rod 121b to be further drawn proximally even though the jaws of tool mechanism are fully closed. This also serves as a safety mechanism to prevent damage to the tissue positioned between the jaw members. As the surgeon squeezes the handles together, latch release spring 140 pivots to allow it to then ride on the opposite side 154 of the cam member 150 when the surgeon releases pressure from pivoting handle 116. Thus, locking block 141 is allowed to move distally under the bias of spring 142.

Figures 9a-9e illustrate the bottom of locking block 141 including diagonal cam member 150 having cam surface 151, triangular recess 152, release cam surface 154, and triangular release cam 153. Figures 9a-9e show block 141 operating in a manner identical to that shown in Figs. 4a-4e, where spring 140 moves along surface 151 into engagement with recess 152 to lock the jaws. To release the block 141, the surgeon further pulls on pivoting handle 116 to engage spring 140 with cam 153, which allows spring 140 to ride along surface 154 until block 141 is fully disengaged.

The instrument of the present invention may be used for electrocautery purposes in addition to its cutting and grasping features. In this regard, as seen in Fig. 8, a coating 123 for insulation purposes may be provided over outer tube 119.

The insulation coating is necessary to avoid damage to surrounding tissue, thus providing the electrocautery feature at only the jaw mechanism. The insulation coating must conform to the shape of the body assembly to allow for smooth passage of the instrument through a cannula of a trocar to the surgical site, without snagging or abrading. Damage to the insulation coating may lead to an electrical path from the instrument to the cannula (typically constructed of a metallic material), thus damaging the surrounding tissue and exposing the surgical team to an electrical shock hazard. Therefore, the insulation must maintain its integrity during use and be resistant to abrasion. Furthermore, it must be uniform in thickness about the instrument to eliminate friction or abrasion as the instru-

ment passes through a trocar assembly in a smooth and unobstructed manner.

In this regard, while heat shrink tubing, and coatings such as PTFE (Teflon), urethane and epoxies may provide suitable insulation for the surgical instrument having an electrocautery feature, in the preferred embodiment of the present invention the body assembly is coated with a polymer such as diparaxylylene, which is a completely linear and highly crystalline material, manufactured by Union Carbide Corporation and known as parylene. Parylene provides a pin-hole free coating which is biocompatible and completely conforms to the shape of the instrument in a uniform manner. Parylene is applied in a vapor-deposition process in a vacuum chamber. During the application of parylene, the parylene layer builds uniformly with equal thickness on the entire surface of the instrument.

Claims

1. An endoscopic or laparoscopic surgical instrument comprising:

a handle assembly including a barrel portion, stationary handle and a pivoting handle;

a body assembly comprising a pair of coaxial members attached at one end to said handle assembly, including an inner rod member slidable within an outer tube member in response to movement of said pivoting handle of said handle assembly, said body assembly terminating at an end remote from said handle assembly in a reciprocatingly movable tool mechanism; and

means positioned within said barrel portion of said handle assembly for locking said tool mechanism said locking means being movable in a first direction a first distance to lock said tool mechanism, and being movable a second distance in said first direction to release said tool mechanism.

2. A surgical instrument according to Claim 1, wherein said locking means comprises means engageable with said inner rod member.

3. A surgical instrument according to Claim 1, wherein said locking means comprises a pivoting braking means for engaging said inner rod, a latch spring and a trigger mechanism for activating and deactivating said braking means.

4. A surgical instrument according to Claim 3, wherein said braking means permits movement of said inner rod in said first direction when said locking means is engaged, and prevents movement of said inner rod in a second direc-

- tion opposite to said first direction when said locking means is engaged.
5. A surgical instrument according to Claim 1, wherein said locking means comprises a camming member having a retaining notch and a latch spring, said latch spring engaging said notch to lock said tool mechanism. 5
 6. A surgical instrument according to Claim 5, wherein said locking means further comprises a release tab for releasing said latch spring, said release tab engaging said latch spring upon movement of said locking means in said first direction. 10
 7. A surgical instrument according to Claim 5, said locking means further comprising a trigger member for advancing said camming member in relation to said latch spring to a locking position. 20
 8. A surgical instrument according to Claim 1, wherein said locking means is secured to said inner rod member and includes a cam surface which engages a latch spring to lock said tool mechanism. 25
 9. An endoscopic or laparoscopic surgical instrument comprising:
 - a handle assembly including a barrel portion, stationary handle and a pivoting handle for incrementally opening and closing a tool mechanism;
 - a body assembly including an inner rod member coaxially disposed within an outer tube member;
 - an inner rod member reciprocatingly slidable within said outer tube in response to movement of said handle assembly, said body assembly terminating at an end remote from said handle assembly in a reciprocatingly movable tool mechanism; and
 - a locking mechanism positioned within said barrel portion of said handle assembly, said locking mechanism including brake means, a latch spring and a trigger member for locking of said tool mechanism.
 10. A surgical instrument according to Claim 9, wherein said trigger member pivots said braking means into engagement with said inner rod member, said trigger member being movable a first distance in a first direction to lock a position of said tool mechanism, and further being movable a second distance in said first direction to release said tool mechanism. 50
 11. A surgical instrument according to Claim 3 or 9, wherein said trigger member includes a camming surface for engaging said latch spring, said braking means pivoting out of engagement with said inner rod when said latch spring is out of engagement with said camming surface, and said latch spring locking said braking means in frictional engagement with said inner rod when said camming surface is engaged with said latch spring.
 12. An endoscopic or laparoscopic surgical instrument comprising:
 - a handle assembly including a barrel portion, stationary handle and a pivoting handle;
 - a body assembly comprising a pair of coaxial members attached at one end to said handle assembly, including an inner rod member slidable within an outer tube member in response to movement of said handle assembly, said body assembly terminating at an end remote from said handle assembly in a reciprocatingly movable tool mechanism; and
 - a locking mechanism positioned within said barrel portion of said handle assembly, said locking mechanism including a latch spring and a locking block for the locking of said tool mechanism.
 13. A surgical instrument according to Claim 12, wherein said pivotable handle activates said inner rod member, such that movement of said pivotable handle slidingly reciprocates said inner rod member within said outer tube member. 30
 14. A surgical instrument according to Claim 12, wherein said locking block is secured to said inner rod member and includes a camming surface, said inner rod when being free to move within said outer tube member when said latch spring is out of engagement with said camming surface, and said latch spring locking said inner rod when said latch spring engages a notch on said camming surface. 35
 15. A surgical instrument according to Claim 14, wherein said locking block is movable a first distance in a first direction to engage said latch spring in said notch, and is movable a second distance in said first direction to disengage said latch spring from said notch. 40
 16. A handle for endoscopic and laparoscopic surgical instruments, said instrument including a body assembly secured to said handle, a tool mechanism secured at a distal end of said body assembly, said body assembly having an 45

inner rod member coaxially slidable within an outer tube member; said handle comprising:

- a pivotable handle;
- a stationary handle;
- a barrel portion; and

a locking mechanism positioned within said barrel portion for engaging said inner rod member to selectively lock said tool mechanism in a closed position.

17. A handle according to Claim 16, wherein said pivotable handle activates said inner rod member, such that movement of said inner rod member within said outer tube member a first distance in a first direction locks said locking mechanism, and movement of said inner rod member a second distance in said first direction releases said locking mechanism.
18. A handle according to Claim 17, wherein said locking mechanism includes a block secured to said inner rod member, said block having a camming surface upon which a latch spring rides during movement said first distance, said latch spring engaging a notch in said camming surface to lock said tool mechanism.
19. A handle according to Claim 3, 10 or 16, wherein said locking mechanism further comprises a brake member which engages said inner rod member to lock said tool mechanism.
20. A handle according to Claim 3, 9 or 19, wherein said brake member includes an aperture concentrically aligned with said inner rod member when said locking mechanism is disengaged, said aperture being eccentric with said inner rod member when said locking mechanism is engaged to frictionally engage said rod member.
21. A surgical instrument according to Claim 1, 9 or 12, wherein said surgical instrument further comprises an electrical insulating means and an electrocautery means.
22. An endoscopic or laparoscopic surgical instrument comprising:
 - a handle assembly including a barrel portion, stationary handle and a pivoting handle;
 - a body assembly comprising a pair of coaxial members attached at one end to said handle assembly, including an inner rod member slidable within an outer tube member in response to movement of said pivoting handle of said handle assembly, said body assembly terminating at an end remote from said handle assembly in a reciprocatingly movable tool

mechanism; and

means positioned within said barrel portion of said handle assembly for engaging said inner rod member to lock said tool mechanism.

23. A surgical instrument according to Claim 22, wherein said engaging means comprises a pivoting braking means for engaging said inner rod, a latch spring and a trigger mechanism for activating and deactivating said braking means.




FIG. 1




FIG. 2




FIG. 3




Fig. 4a





Fig. 4.b






Fig. 4.d




Fig. 4c




Fig. 5




Fig. 6




FIG. 7




FIG. 8




Fig. 9a




Fig. 9b




Fig. 9c




Fig. 9d




Fig. 9e




Fig. 10




FIG. 11



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 93 10 5678

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
X	US-A-4 614 187 (J. S. MULHOLLAN)	9,12,13, 16-19, 22,23	A61B17/28
A	* column 4, line 1 - line 56 *	1-4	
E	EP-A-0 543 107 (U.S. SURGICAL CORPORATION)	9,12,13, 16-19, 22,23	
	* column 11, line 15 - column 12, line 6 *		
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			A61B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 06 JULY 1993	Examiner GERARD B.
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : member of the same patent family, corresponding document	